

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
3.5"	MV-35F	960 x 240	LCD Monitor	2 Composite (BNC Loop-Thru), NTSC/PAL	4:3	250 nits	12VDC
3.5"	MVF-35F	960 x 240	Flip-Down LCD Monitor	2 Composite (BNC Loop-Thru), NTSC/PAL	4:3	250 nits	12 VDC
4.3"	RVM-43F	960 x 234	Rear View Mirror LCD Monitor	Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	12 VDC
4.3"	VMTR-4.3V	480 x 272	Resistive Touch Screen LCD Monitor	VGA	4:3	350 nits	12 VDC
5"	RM-555G	800 x RGB x 480	Triple 5" Rack Mount LCD Monitor Metal Housing	VGA, Analog RGB, S-Video, Component, Composite (BNC Loop-Thru), NTSC/PAL	4:3	350 nits	12 VDC / 90-240 VAC
5.5"	VM-5K	960 x 234	Portable Handheld LCD Monitor Kit	Composite (BNC Loop-Thru), NTSC/PAL	4:3	500 nits	12 VDC
7"	RM-77G	800 x RGB x 480	Dual 7" Rack Mount LCD Monitor Metal Housing	VGA, S-Video, Component (YbPr), Analog RGB, Composite (BNC Loop-Thru), NTSC/PAL	4:3	500 nits	12 VDC / 90-240 VAC
7"	RML-77B	800 x RGB x 480	Low-Cost Dual 7" Rack Mount LCD Monitor Metal Housing	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	500 nits	12 VDC / 90-240 VAC
7"	MV-7F	960 x 234	LCD Monitor	Composite (BNC Loop-Thru), NTSC/PAL	16:9	300 nits	12 VDC
7"	MVF-7F	1440 x 234	Flip-Down LCD Monitor	2 Composite (BNC Loop-Thru), NTSC/PAL	16:9	350 nits	12 VDC
7"	MVW-7F	1440 x 234	Widescreen LCD Monitor	2 Composite (BNC Loop-Thru), NTSC/PAL	16:9	300 nits	12 VDC (Opt 12-32 VDC)
7"	MVQT-72F	1440 x 234	Resistive Touch Screen Quad LCD Monitor Metal Housing	4 Composite (BNC Loop-Thru), NTSC/PAL	16:9	300 nits	10-36 VDC
7"	VM-7X	800 x RGB x 480	LCD Monitor Metal Housing	Composite (BNC Loop-Thru), NTSC/PAL	16:9	500 nits	12 VDC
7"	VMTR-7N	800 x RGB x 480	Resistive Touch Screen LCD Monitor Metal Housing	VGA, 2 x BNC, NTSC/PAL	16:9	250 nits	12 VDC
8.4"	SRM-8.4A	800 x 600 (SVGA)	Sunlight Readable LCD Monitor Metal Housing	VGA, S-Video & Composite (BNC Loop-Thru), (RCA Connector); NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
8.4"	SRM-8.4B	800 x 600 (SVGA)	Sunlight Readable LCD Monitor Metal Housing	VGA, BNC Loop-Thru, NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
8.4"	VM-8.4A	800 x 600 (SVGA)	LCD Monitor Metal Housing	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	450 nits	12 VDC / 90-240 VAC
8.4"	VM-8.4B	800 x 600 (SVGA)	LCD Monitor Metal Housing	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	450 nits	12 VDC / 90-240 VAC
8.4"	VMOB-8.4A	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor Metal Housing	VGA, S-Video & Composite (BNC Loop-Thru), (RCA Connector); NTSC/PAL	4:3	600 nits	12 VDC / 90-240 VAC
8.4"	VMOB-8.4B	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor Metal Housing	VGA, BNC Loop-Thru, NTSC/PAL	4:3	600 nits	12 VDC / 90-240 VAC

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
8.4"	VMOBT-8.4B	800 x 600 (SVGA)	Daylight Readable Optically Bonded Resistive Touch Screen LCD Monitor Metal Housing	VGA, BNC Loop-Thru, NTSC/PAL	4:3	600 nits	12 VDC / 90-240 VAC
10.4"	EPTR-10.4V	800 x 600 (SVGA)	Touch Screen LCD Monitor with Embedded PC	VGA	4:3	400 nits	12 VDC / 90-240 VAC
10.4"	MMTR-10.4V	800 x 600 (SVGA)	Medical-Grade Touch Screen LCD Display	VGA	4:3	400 nits	12 VDC / 90-240 VAC
10.4"	SRM-10.4A	800 x 600 (SVGA)	Sunlight Readable LCD Monitor Metal Housing	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
10.4"	SRM-10.4B	800 x 600 (SVGA)	Sunlight Readable LCD Monitor Metal Housing	Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
10.4"	VM-10.4A	800 x 600 (SVGA)	LCD Monitor Metal Housing	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 100-240 VAC
10.4"	VM-10.4B	800 x 600 (SVGA)	LCD Monitor Metal Housing	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 100-240 VAC
10.4"	VMOB-10.4A	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor Metal Housing	VGA, S-Video & Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 100-240 VAC
10.4"	VMOB-10.4B	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor Metal Housing	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 100-240 VAC
10.4"	VMOBT-10.4B	800 x 600 (SVGA)	Daylight Readable Optically Bonded Resistive Touch Screen LCD Monitor Metal Housing	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC
10.4"	VMTR-10.4V	800 x 600 (SVGA)	Resistive Touch Screen LCD Monitor Metal Housing	VGA	4:3	400 nits	12 VDC / 90-240 VAC
12"	SRM-12A	800 x 600 (SVGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
12"	SRM-12B	800 x 600 (SVGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
12"	SRM-12C	800 x 600 (SVGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, DVI	4:3	1,000 nits	12 VDC / 90-240 VAC
12"	SRMTR-12B	800 x 600 (SVGA)	Sunlight Readable Touch Screen LCD Monitor 600:1 Contrast Ratio	VGA, Composite	4:3	1,000 nits	12 VDC / 90-240 VAC
12"	SMTR-12COF	800 x 600 (SVGA)	Sunlight Readable Touch Screen LCD Monitor 600:1 Contrast Ratio	VGA, DVI	4:3	1,000 nits	12 VDC / 90-240 VAC
12"	VM-12A	800 x 600 (SVGA)	LCD Monitor	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC
12"	VM-12B	800 x 600 (SVGA)	LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC
12"	VM-12C	800 x 600 (SVGA)	LCD Monitor	VGA, DVI	4:3	400 nits	12 VDC / 90-240 VAC
12"	VMOB-12A	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC
12"	VMOB-12B	800 x 600 (SVGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru); NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC
12"	VMOBTC-12B	800 x 600 (SVGA)	Optically Bonded Capacitive Touch LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	400 nits	12 VDC / 90-240 VAC

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
15"	SRM-15A	1024 x 768 (XGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
15"	SRM-15B	1024 x 768 (XGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1,000 nits	12 VDC / 90-240 VAC
15"	SRMH-15A	1024 x 768 (XGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1.300 nits	12 VDC / 90-240 VAC
15"	SRMH-15B	1024 x 768 (XGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	1.300 nits	12 VDC / 90-240 VAC
15"	SRMH-15C	1024 x 768 (XGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, DVI	4:3	1.300 nits	12 VDC /
15"	SRMTC-15N	1024 x 768 (XGA)	Sunlight Readable Touch Screen LCD Monitor 700:1 Contrast Ratio	VGA, BNC	4:3	1,000 nits	90-240 VAC
15"	VM-15A	1024 x 768 (XGA)	LCD Monitor	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	350 nits	12 VDC / 90-240 VAC
15"	VML-15AL	1024 x 768 (XGA)	Low-Cost LCD Monitor	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	250 nits	12 VDC / 90-240 VAC
15"	VM-15B	1024 x 768 (XGA)	LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	350 nits	12 VDC / 90-240 VAC
15"	VML-15BL	1024 x 768 (XGA)	Low-Cost LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	250 nits	12 VDC / 90-240 VAC
15"	VM-15C	1024 x 768 (XGA)	LCD Monitor	VGA, DVI	4:3	350 nits	12 VDC / 90-240 VAC
15"	VML-15CL	1024 x 768 (XGA)	Low-Cost LCD Monitor	VGA, DVI	4:3	250 nits	12 VDC / 90-240 VAC
15"	VMOB-15A	1024 x 768 (XGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, S-Video, Composite (RCA), NTSC/PAL	4:3	350 nits	12 VDC / 90-240 VAC
15"	VMOB-15B	1024 x 768 (XGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, Composite Video Loop-Thru, NTSC/PAL Auto-Recognition	4:3	350 nits	12 VDC / 90-240 VAC
15"	VMOB-15C	1024 x 768 (XGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, DVI	4:3	350 nits	12 VDC / 90-240 VAC
15"	VMOBH-15B	1024 x 768 (XGA)	Daylight Readable Optically Bonded LCD Monitor 1,200:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru),	4:3	550 nits	12 VDC / 90-240 VAC
15"	VMTC-15V	1024 x 768 (XGA)	Capacitive Touch Screen LCD Monitor	VGA	4:3	250 nits	12 VDC / 90-240 VAC
15"	VMTR-15C	1024 x 768 (XGA)	Resistive Touch Screen LCD Monitor	VGA, DVI	4:3	350 nits	12 VDC / 90-240 VAC
15"	VMTS-15C	1024 x 768 (XGA)	SAW Touch Screen LCD Monitor	VGA, DVI	4:3	250 nits	12 VDC / 90-240 VAC
17"	MM-17B	1280 x 1024 (SXGA)	Medical-Grade LCD Display Meets UL-60601-1	VGA, Composite (BNC Loop-Thru), NTSC/PAL	5:4	300 nits	12 VDC / 90-240 VAC
17"	MM-17J	1280 x 1024 (SXGA)	Medical-Grade LCD Display Meets UL-60601-1	VGA, DVI- Composite (BNC Loop-Thru)	5:4	380 nits	12 VDC / 90-240 VAC

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
17"	SRM-17B	1280 x 1024 (SXGA)	Sunlight Readable LCD Monitor 600:1 Contrast Ratio	VGA, Composite (BNC Loop-Thru), NTSC/PAL	5:4	1,000 nits	12 VDC / 90-240 VAC
17"	VM-17A	1280 x 1024 (SXGA)	LCD Monitor	VGA, S-Video, Composite (RCA) (BNC Loop-Thru), NTSC/PAL	5:4	300 nits	12 VDC / 90-240 VAC
17"	VM-17B	1280 x 1024 (SXGA)	LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	5:4	300 nits	12 VDC / 90-240 VAC
17"	VM-17C	1280 x 1024 (SXGA)	LCD Monitor	VGA, DVI	5:4	300 nits	12 VDC / 90-240 VAC
17"	VM-17D	1280 x 1024 (SXGA)	LCD Monitor	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL	5:4	420 nits	90-240 VAC
17"	VM-17P	1280 x 1024 (SXGA)	LCD Monitor	VGA, HD-SDI, S-Video, Component (YCbCr), Composite (BNC Loop-Thru)	5:4	420 nits	12 VDC / 90-240 VAC
17"	VM-17B-24V	1280 x 1024 (SXGA)	24 VDC LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	5:4	300 nits	24 VDC
17"	VM-17J-24V	1280 x 1024 (SXGA)	24 VDC LCD Monitor	DVI, BNC and VGA (via included DVI to VGA adapter)	5:4	300 nits	24 VDC
17"	VMTCH-17C	1280 x 1024 (SXGA)	Capacitive Touch Screen LCD Monitor	VGA, DVI	5:4	380 nits	12 VDC / 90-240 VAC
17"	VMTR-17V	1280 x 1024 (SXGA)	Resistive Touch Screen LCD Monitor 800:1 Contrast Ratio	VGA	5:4	300 nits	12 VDC / 90-240 VAC
17"	VMTRH-17C	1280 x 1024 (SXGA)	Resistive Touch Screen LCD Monitor 1,000:1 Contrast Ratio	VGA, DVI	5:4	380 nits	12 VDC / 90-240 VAC
18.5"	RMTR-18.5V	1366 x 768 (WXGA)	Rack Mount Resistive Touch Screen LCD Monitor 19" Metal Enclosure	VGA, DVI, HDMI	16:9	300 nits	12 VDC / 90-240 VAC
18.5"	VMTR-18.5V	1366 x 768 (WXGA)	Resistive Touch Screen LCD Monitor	VGA	16:9	300 nits	12 VDC / 90-240 VAC
19"	MM-19J	1280 x 1024 (SXGA)	Medical-Grade LCD Display Meets UL-60601-1	VGA, DVI & BNC	4:3	300 nits	12 VDC / 90-240 VAC
19"	SRM-19C	1280 x 1024 (SXGA)	Sunlight Readable LCD Monitor	VGA & DVI	4:3	1,000 nits	12 VDC / 90-240 VAC
19"	VM-19A	1280 x 1024 (SXGA)	LCD Monitor	VGA, S-Video, Composite, NTSC/PAL	4:3	300 nits	12 VDC / 90-240 VAC
19"	VML-19AL	1280 x 1024 (SXGA)	Low-Cost LCD Monitor	VGA, S-Video, Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	12 VDC / 90-240 VAC
19"	VM-19B	1280 x 1024 (SXGA)	LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	12 VDC / 90-240 VAC
19"	VML-19BL	1280 x 1024 (SXGA)	Low-Cost LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	12 VDC / 90-240 VAC
19"	VM-19C	1280 x 1024 (SXGA)	LCD Monitor	VGA, DVI	4:3	300 nits	12 VDC / 90-240 VAC
19"	VML-19CL	1280 x 1024 (SXGA)	Low-Cost LCD Monitor	VGA, DVI	4:3	300 nits	12 VDC / 90-240 VAC
19"	VML-19BL-24V	1280 x 1024 (SXGA)	24 VDC LCD Monitor	VGA, Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	24 VDC
19"	VML-19CL-24V	1280 x 1024 (SXGA)	24 VDC LCD Monitor	VGA, DVI	4:3	300 nits	24 VDC

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
19"	VML-19J-24V	1280 x 1024 (SXGA)	24 VDC LCD Monitor	DVI-I, BNC and VGA (via included DVI to VGA adapter)	4:3	300 nits	24 VDC
19"	VMTR-19C	1280 x 1024 (SXGA)	Resistive Touch Screen LCD Monitor	VGA, DVI	4:3	300 nits	12 VDC / 90-240 VAC
19"	VMTR-19V	1280 x 1024 (SXGA)	Resistive Touch Screen LCD Monitor	VGA USB & RS-232	4:3	300 nits	12 VDC / 90-240 VAC
20"	VM-20E	1600 x 1200 (UXGA)	LCD Monitor	VGA, Component (YCbCr), S-Video, DVI, Composite (BNC Loop-Thru), NTSC/PAL	4:3	300 nits	24 VDC / 90-240 VAC
21.5"	SRM-21.5C	1920 x 1080 (Full HD)	Full HD Sunlight Readable LCD Monitor	VGA, DVI	16:9	1,000 nits	12 VDC / 90-240 VAC
21.5"	SRMOB-21.5C	1920 x 1080 (Full HD)	Full HD Optically Bonded and Sunlight Readable LCD Monitor	VGA, DVI	16:9	1,000 nits	12 VDC / 90-240 VAC
22"	MM-22C	1680 x 1050 (WSXGA)	HD Medical-Grade LCD Display Meets UL-60601-1	VGA, DVI	16:9	300 nits	90-260 VAC
22"	MMTR-22C	1680 x 1050 (WSXGA)	HD Medical-Grade Touch Screen LCD Display Meets UL-60601-1	VGA, DVI	16:9	300 nits	90-260 VAC
22"	VM-22C	1680 x 1050 (WSXGA)	HD LCD Monitor	VGA, DVI	16:10	300 nits	90-260 VAC
22"	VM-22E	1680 x 1050 (WSXGA)	HD LCD Monitor	VGA, DVI, S-Video, Component, Composite (BNC Loop-Thru),	16:10	300 nits	12 VDC / 90-240 VAC
22"	VMOB-22C	1680 x 1050 (WSXGA)	HD Daylight Readable Optically Bonded LCD Monitor 1,300:1 Contrast Ratio	VGA, DVI	16:10	300 nits	12 VDC / 90-240 VAC
22"	VMOBH-22C	1680 x 1050 (WSXGA)	HD Optically Bonded LCD Monitor	VGA, DVI	16:10	300 nits	12 VDC / 90-240 VAC
22"	VMTR-22R	1680 x 1050 (WSXGA)	HD Resistive Touch Screen LCD Monitor	VGA, DVI, HDMI	16:10	300 nits	12 VDC / 90-240 VAC
22"	VMTRH-22C	1680 x 1050 (WSXGA)	HD Resistive Touch Screen LCD Monitor HD Compliant 178° Viewing Angle	VGA, DVI	16:10	300 nits	12 VDC / 90-240 VAC
26"	VM-26D	1366 x 768 (WXGA)	720p HD LCD Monitor Metal Housing	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL	16:9	500 nits	24 VDC / 90-240 VAC
26"	VMTC-26C	1366 x 768 (WXGA)	720p HD Capacitive Touch Screen LCD Monitor	VGA, DVI	16:9	450 nits	24 VDC / 90-240 VAC
27"	VM-27R	1920 x 1080 (Full HD)	Full HD LCD Monitor	VGA, DVI, HDMI	16:9	300 nits	12 VDC / 90-260 VAC
27"	VMTC-27C	1920 x 1080 (Full HD)	Full HD Capacitive Touch Screen LCD Monitor	VGA, DVI, HDMI (via adapter)	16:9	300 nits	12 VDC / 90-240 VAC
32"	VM-32D	1920 x 1080 (Full HD)	Full HD LCD Monitor Metal Housing	VGA, HDMI, Composite (BNC Loop-Thru),, NTSC/PAL	16:9	500 nits	24 VDC / 90-240 VAC
32"	VM-32D2	1366 x 768 (WXGA)	720p HD LCD Monitor Metal Housing	VGA, HDMI, Composite (BNC Loop-Thru), NTSC/PAL	16:9	500 nits	24 VDC / 90-240 VAC
32"	VMTC-32C	1366 x 768 (WXGA)	720p HD Capacitive Touch Screen LCD Monitor Metal Housing	VGA, DVI	16:9	450 nits	24 VDC / 90-250 VAC
42"	VM-42E	1920 x 1080 (Full HD)	Full HD LCD Monitor Metal Housing	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL	16:9	500 nits	90-240 VAC

Industrial LCD Monitor Selector Guide

Screen Size	Model No.	Max Resolution	Description	Video Inputs	Aspect Ratio	Brightness	Voltage
42"	VM-42H	1920 x 1080 (Full HD)	Full HD LCD Monitor Metal Housing	VGA, HDMI	16:9	500 nits	90-240 VAC
42"	VMTIH-42C	1920 x 1080 (Full HD)	Full HD Infra Red Touch Screen LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, DVI	16:9	500 nits	90-240 VAC
42"	VMTIH-42H	1920 x 1080 (Full HD)	Full HD Infra Red Touch Screen LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, HDMI	16:9	500 nits	90-240 VAC
46"	VM-46E	1920 x 1080 (Full HD)	Full HD LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru), NTSC/PAL	16:9	500 nits	100-260 VAC
46"	VM-46H	1920 x 1080 (Full HD)	Full HD LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, HDMI	16:9	500 nits	100-260 VAC
52"	VM-52E	1920 x 1080 (Full HD)	Full HD LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, S-Video, DVI, Component (YCbCr), Composite (BNC Loop-Thru)	16:9	700 nits	90-260 VAC
52"	VM-52H	1920 x 1080 (Full HD)	Full HD LCD Monitor 5,000:1 Contrast Ratio Metal Housing	VGA, HDMI	16:9	700 nits	90-260 VAC

Nearly all monitors can be customized/modified to meet your requirements. All models can be private-labelled. Visit www.Tru-VuMonitors.com for more information. All specifications subject to change. Contact *TRU-Vu* for the latest specs.