



### SRMH-15 Series

#### 15" Sunlight-Readable Monitors

- Produces Clear, Sharp Images Even in Direct Bright Sunlight
- 1,300 nits Brightness
- LED Backlights
- High Shock & Vibration Resistance
- Lockable OSD Controls
- High Uniformity (90%)
- Low EMI Noise
- 3 Year Warranty

The SRMH-15 Series Sunlight Readable LCD monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. They utilize state-of-the-art LED backlights to produce over 1,300 nits of brightness (vs. 250-300 nits for standard monitors). This results in amazingly bright, crystal-clear images, even with direct, bright sunlight on the face of the screen. The SRMH-15 Series Sunlight Readable monitors are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, inspection, advertising and transportation applications where viewability in direct bright sunlight is crucial.

All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.


### Specifications

MODEL	SRMH-15A	SRMH-15B	SRMH-15C
LCD Panel	15" Color TFT LCD Monitor		
Resolution	1024 x 768 (XGA)		
Image Size (mm)	11.97" (W) x 8.98" (H)		
Pixel Pitch	0.297mm x 0.297mm		
Display Colors	16.2 Million		
Aspect Ratio	4:3		
Brightness	1,300 nits		
Contrast Ratio	700:1		
Viewing Angle	140° (H) x 130° (V)		
Response Time	12 msec (gray to gray)		
Control	OSD (On-Screen Display) via Front Panel Pushbuttons		
Video Inputs	VGA, S-Video, Composite (BNC Loop-Thru) NTSC/PAL Auto-Recognition	VGA, Composite (BNC Loop-Thru) NTSC/PAL Auto-Recognition	VGA, DVI
Analog Video In / Out	1 RCA Input	1 BNC Input/ 1 BNC Output	
In / Output Impedance	75Ω / Auto Terminating Output		
Power Requirement	12 VDC (90-240 VAC with Included Power Brick)		
Power Consumption	50 Watts		
Enclosure	ABS		
Mounting	Included Base or 75x75mm VESA Hole Pattern		
Operating Temperature	32° to 122° F / 0° to 50° C		
Humidity	5-90% RH		
Shock	50 G (20 msec, 1/2 sine)		
Vibration	1.5G RMS 10-200 HZ		
Approvals	UL/cUL, FCC, CE, TUV, RoHS		
Dimensions	13.7" (W) x 10.9" (H) x 1.5" (D) / 347.97 (W) x 276.86 (H) x 38.09 (D) mm		
Weight	6.2 lbs. / 2.8 kg		

## SRMH-15 Series

15" Sunlight Readable LCD Monitors

### Dimensions



### Standard Accessories:

- 90-240 VAC Power Brick
- Benchtopy Stand
- VGA Cable

### Available Options:

- Protective/Anti-Reflective Glass Screen
- Panel Mount
- Rack Mount
- Open-Frame Configuration
- Private Label
- Other Customer - Specific Modifications