

VMLTR-19CL

Touch Screen Monitor



- 19" 5-Wire Resistive Touch Screen
- USB Controller
- High Resolution: 1280 x 1024 (SXGA)
- Wide Viewing Angle (160°)
- Video Inputs: VGA & DVI-D
- 300 Nits Brightness
- 800:1 Contrast Ratio
- Lockable OSD Controls
- Can Be Customized to Meet Your Needs
- 3 Year Warranty

TRU-Vu industrial LCD monitors are specifically designed for use in demanding industrial, commercial, medical and A/V applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability.

The VMLTR-19CL 19" Touch Screen monitor utilizes 5-wire resistive touch technology; the screen can be activated via a finger, gloved hand, credit card or stylus. The image quality is exceptionally clear and bright; the contact activation point is extremely accurate; and it features USB interface. An extensive list of OEM options enables you to customize the VMLTR-19CL to meet your exact needs. Visit www.TRU-VuMonitors.com for more details.

Specifications

LCD Panel	19" TFT Color LCD
Touch Screen Type	5-Wire Resistive Touch
Touch Screen Interface	USB
Resolution	1280 x 1024 (SXGA)
Display Area	14.81" (W) x 11.85" (H)
Pixel Pitch	0.294mm x 0.294mm
Display Colors	16.7M
Aspect Ratio	4:3
Brightness	300 nits
Contrast Ratio	800:1
Viewing Angle	160° (H) x 160° (V)
Response Time	5 msec (gray to gray)
Control	OSD (On-Screen Display) via Front Panel Pushbuttons (may be locked)
Video Inputs	VGA, DVI-D
Power Requirement	12 VDC, 3.0A (90-240 VAC with Included Power Brick)
Enclosure	ABS
Mounting	Mounting Stand (shown) Included; VESA Mounting 75x75mm
Operating Temperature	32° to 132° F / 0° to 55° C
Humidity	5-90% RH
Shock	50 G (20 msec, 1/2 sine)
Vibration	1.5 G RMS 10-200Hz
Approvals	UL/cUL, FCC, CE, TUV, RoHS
Dimensions	16.7" (W) x 15.0" (H) x 2.0" (D) / 424.17 (W) x 381 (H) x 50.8 (D) mm
Weight	11 lbs. / 5 kg
Optional Accessory	MB-RACK19 Rack Mount Bracket